SSG4012 SERIES 4" LOWER CONNECT GLYCERIN FILLED GAUGES

ALL SPECIFICATIONS AND DIMENSIONS SUBJECT TO CHANGE WITHOUT NOTICE

SSG4012 SERIES

- **Case**: 304 Stainless Steel
- **Dial**: Aluminum, White, Black,& Blue Type
- **Scale**: Dual (lb/in^2 - bar - x 100 kpa)
- **Bourdon Tube**: Brass
- **Connection**: Brass 1/4" NPT
- **Lens**: Acrylic
- **Surge Protection**: Standard
- **Accuracy**: ANSI Grade B, 3%-2%-3%

PART#	RANGE
SSG4012-V	30hg-0
SSG4012-C	30Hg-0-30 PSI
SSG4012-15	0-15 PSI
SSG4012-30	0-30 PSI
SSG4012-60	0-60 PSI
SSG4012-100	0-100 PSI
SSG4012-160	0-160 PSI
SSG4012-200	0-200 PSI
SSG4012-300	0-300 PSI
SSG4012-400	0-400 PSI
SSG4012-600	0-600 PSI
SSG4012-1K	0-1000 PSI
SSG4012-1.5K	0-1500 PSI
SSG4012-2K	0-2000 PSI
SSG4012-3K	0-3000 PSI
SSG4012-5K	0-5000 PSI
SSG4012-6K	0-6000 PSI
SSG4012-10K	0-10000 PSI
SSG4012-15K	0-15000 PSI



LSS4012 & 4014 SERIES 4" LOWER CONNECT GLYCERIN FILLED GAUGES

LSS4012 & 4014 SERIES

All Stainless

- **Case**: 304 Stainless Steel
- **Dial**: Aluminum, White, Black,& Blue Type
- **Scale**: Dual (lb/in^2 - bar - x 100 kpa)
- **Bourdon Tube**: 316 Stainless Steel
- **Connection**:
  LSS4012- 316 Stainless Steel 1/4" NPT
  LSS4014- 316 Stainless Steel 1/2" NPT
- **Lens**: Acrylic
- **Surge Protection**: Standard
- **Accuracy**: ANSI Grade B, 3%-2%-3%

PART#	RANGE
SSG401*-V	30hg-0
SSG401*-C	30Hg-0-30 PSI
SSG401*-15	0-15 PSI
SSG401*-30	0-30 PSI
SSG401*-60	0-60 PSI
SSG401*-100	0-100 PSI
SSG401*-160	0-160 PSI
SSG401*-200	0-200 PSI
SSG401*-300	0-300 PSI
SSG401*-400	0-400 PSI
SSG401*-600	0-600 PSI
SSG401*-1K	0-1000 PSI
SSG401*-1.5K	0-1500 PSI
SSG401*-2K	0-2000 PSI
SSG401*-3K	0-3000 PSI
SSG401*-5K	0-5000 PSI
SSG401*-10K	0-10000 PSI
SSG401*-15K	0-15000 PSI

ALL STAINLESS



∗ Denotes Connection 2=1/4"NPT, 4=1/2"NPT