


PART	NPT SIZE	A	B	Cv	MAX PRESSURE
SCI-2	1/4"	2.31	1.35	3.50	800 PSI WOG 125 WSP
SCI-3	3/8"	2.31	1.35	3.50	
SCI-4	1/2"	2.31	1.35	5.20	
SCI-6	3/4"	2.87	1.81	10.00	
SCI-8	1"	3.50	2.13	15.00	
SCI-10	1-1/4"	4.18	2.46	24.50	
SCI-12	1-1/2"	4.93	2.88	25.20	600 PSI WOG 125 WSP
SCI-16	2"	6.00	3.56	52.00	
SCI-20	2-1/2"	7.12	4.53	73.80	
SCI-24	3"	8.13	5.56	113.10	

- NOTES:**
- 316 STAINLESS (CF8M)
 - 1/2 PSI CRACKING PRESSURE
 - PTFE SEAT (BUBBLE TIGHT)
 - TEMP: +10° TO 450°F

THIS DOCUMENT IS PROPERTY OF UNIVERSAL COMPONENTS, INC.
 ANY REPRODUCTION, DISCLOSURE, OR USE OF THIS DOCUMENT IS
 EXPRESSLY PROHIBITED UNLESS OTHERWISE AGREED UPON IN WRITING.
 ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

			
DRAWING NAME: SCI STAINLESS STEEL CHECK VALVE			
MATERIAL: --	A	DRAWING NUMBER: SCI-SERIES	REV. 2
SCALE: N.T.S.	NAME: MCH	DATE: 5/22/2019	